WINTER APPLICATION RESTRICTIONS FOR **NON-AGRICULTURAL SOURCE MATERIALS (NASM)**

O. Reg. 267/03 Part VI

SEWAGE BIOSOLIDS OR ANY OTHER MATERIAL CONTAINING HUMAN BODY WASTE

General prohibition:

The land application of sewage biosolids or any other material containing human body waste is not permitted from December 1 to March 31 or at any time that the soil is frozen or snow covered. O. Reg 267/03 s52.3

DECEMBER 1 TO MARCH 31 WHEN SOIL IS NOT FROZEN NOR SNOW COVERED:

CATEGORY 1 LIQUID NASM CATEGORY 1 SOLID NASM CATEGORY 2 SOLID NASM

Permitted Application Conditions:

Injection

MATERIAL:

- Incorporation same day
- Surface application only if 30% of the land surface is covered Minimum setback from top of bank of surface water: by a living crop or crop residue

Minimum setback from top of bank of surface water:

- 100 metres if the maximum sustained slope is greater than 6% O. Reg 267/03 s52.5(5)
- 20 metres elsewhere

O. Reg 276/03 s52.5(4)

MATERIAL: CATEGORY 2 LIQUID NASM CATEGORY 3 LIQUID NASM*

CATEGORY 3 SOLID NASM*

Permitted Application Conditions:

- Injection
- Incorporation same day
- Surface application only if 30% of the land surface is covered by a living crop or crop residue

Minimum setback from top of bank of surface water:

- 100 metres if the maximum sustained slope is greater than 3% O. Reg 267/03 s52.5(3)
- 20 metres elsewhere

O. Reg 267/03 s52.5(2)

ANY TIME THAT SOIL IS FROZEN OR SNOW **COVERED:**

MATERIAL: CATEGORY 1 LIQUID NASM

> **CATEGORY 1 SOLID NASM CATEGORY 2 SOLID NASM**

Permitted Application Conditions:

- Injection
- Incorporation within 6 hours of application

- 100 metres if the maximum sustained slope is greater than 6%
- 20 metres elsewhere

MATERIAL: CATEGORY 2 LIQUID NASM

CATEGORY 3 LIQUID NASM CATEGORY 3 SOLID NASM*

Permitted Application Conditions:

- Injection
- Incorporation within 6 hours of application

Minimum setback from top of bank of surface water:

- 100 metres if the maximum sustained slope is greater than 3%
- 20 metres elsewhere

NOTES: * Does not include sewage biosolids or material containing human body waste.

A vegetated buffer zone is required between the field and any adjacent surface water when a NASM application area is part of the land included in a nutrient management plan.

